



Southern Pipe, Inc.

P. O. Box 606, 135 Random Drive, New London, NC 28127
Phone: 704-463-5202 Fax: 704-463-5203 www.southern-pipe.com

**TYPE EB – 35 (ENCASED BURIAL) HEAVY WALL TC-8
RIGID PVC NONMETALLIC CONDUIT
FOR CONCRETE ENCASUREMENT UNDERGROUND**

Southern Pipe Type EB-35 (Encased Burial Utility Duct) rigid PVC conduit is manufactured for use in outside concrete encasement applications. Type EB-35 is manufactured in accordance with the following industry standards:

National Electrical Manufacturers Association (NEMA)
American Society for Testing and Materials (ASTM)
National Electrical Code (NEC)

TC-8
F-512
300-5 & 710-3(b)

SIZE	PART NUMBER	DESCRIPTION	MIN WALL	O.D.	WEIGHT PER 100 FEET	PALLET QTY
2"	62820	20 FT/B.E.	.060	2.375	36	2800
3"	82630	20 FT/B.E.	.076	3.500	63	1760
3 1/2"	82635	20 FT/B.E.	.088	4.000	85	1260
4"	82640	20 FT/B.E.	.100	4.500	94	1140
5"	82650	20 FT/B.E.	.126	5.563	140	760
6"	82660	20 FT/B.E.	.152	6.625	228	520

RUS listed

MANUFACTURER OF QUALITY PVC ELECTRICAL CONDUIT PRODUCTS



Southern Pipe, Inc.

P. O. Box 606, 135 Random Drive, New London, NC 28127
Phone: 704-463-5202 Fax: 704-463-5203 www.southern-pipe.com

**TYPE DB-120 (DIRECT BURIAL) TC-8
RIGID PVC NONMETALLIC CONDUIT
FOR DIRECT BURIAL UNDERGROUND**

Southern Pipe Type DB-120 (DIRECT BURIAL) rigid PVC conduit is manufactured for direct burial underground. Type DB-120 TC-8 is manufactured in accordance with the following industry standards.

National Electrical Manufacturers Association (NEMA)
American Society for Testing and Materials (ASTM)

TC-8
F-512

SIZE	PART NUMBER	DESCRIPTION	MIN WALL	O.D.	WEIGHT PER 100 FEET	PALLET QTY
2"	82820	20 FT/B.E.	.077	2.375	43	2800
3"	82830	20 FT/B.E.	.118	3.500	91	1760
3 1/2"	82835	20 FT/B.E.	.136	4.000	115	1260
4"	82840	20 FT/B.E.	.154	4.500	150	1140
5"	82850	20 FT/B.E.	.191	5.563	1230	760
6"	82860	20 FT/B.E.	.227	6.625	310	520

RUS listed

MANUFACTURER OF QUALITY PVC ELECTRICAL CONDUIT PRODUCTS