


Southern Pipe	Trade	T Min	OD	E	B	D Min	C	R	L
Part Number	Size	Wall Thickness	Outside Diameter	Bell Entrance ID	Bell Bottom ID	Bell Depth	Chamfer Angle	Reference Mark	Total Length
62820	2"	0.060	2.375	2.387	2.369	2.500	30°	2.500	240
62830	3"	0.092	3.500	3.516	3.492	3.625	30°	3.625	240
62835	3 1/2"	0.107	4.000	4.016	3.992	3.875	30°	3.875	240
62840	4"	0.121	4.500	4.518	4.491	4.125	30°	4.125	240
62850	5"	0.152	5.563	5.583	5.553	4.750	30°	4.750	240
62860	6"	0.182	6.625	6.647	6.614	5.750	30°	5.750	240

RUS Listed
 NEMA TC 6
 NEMA TC 18
 ASTM F-512
 For Direct Burial



TC 6 DB-60 Rigid Non-Metallic PVC Utility Duct
 Minimum Modulus of Elasticity 500,000 psi

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES
 All Dimensions are Nominal

NAME		DATE
DRAWN	K. Mitchell	04/01/13
CHECKED		
ENG APPR		
FILE: TC 6 DB-60.dft		REV 10