


Southern Pipe Part Number	Trade Size	T Min Wall Thickness	OD Outside Diameter	ID Inside Diameter	E Bell Entrance ID	B Bell Bottom ID	D Min Bell Depth	C Chamfer Angle	R Reference Mark	L Total Length
21430	3"	0.216	3.500	3.008	3.515	3.492	3.625	30°	3.625	120
21440	4"	0.237	4.500	3.961	4.515	4.491	4.125	30°	4.125	120
21450	5"	0.258	5.563	4.975	5.593	5.553	1.750	30°	4.750	120
21460	6"	0.280	6.625	5.986	6.658	6.614	5.750	30°	5.750	120
21480*	8"	0.322	8.625	7.853	8.670	8.610	6.750	30°	6.750	120
25430	3"	0.216	3.500	3.008	3.515	3.492	3.625	30°	3.625	240
25440	4"	0.237	4.500	3.961	4.515	4.491	4.125	30°	4.125	240
25450	5"	0.258	5.563	4.975	5.593	5.553	1.750	30°	4.750	240
25460	6"	0.280	6.625	5.986	6.658	6.614	5.750	30°	5.750	240
25480*	8"	0.322	8.625	7.853	8.670	8.610	6.750	30°	6.750	240

*8" is Non UL-Listed

 Listed 651
 NEMA TC 2
 Sunlight Resistant
 See NEC Article 352 for Usage

RUS Listed
 NEMA TC 18
 90° C Wire

 *Southern Pipe, Inc.*

Schedule 40 Cellular Core Rigid Non-Metallic PVC Conduit

	NAME	DATE
DRAWN	K. Mitchell	04/01/13
CHECKED		
ENG APPR		
FILE: SCH 40 So-Lite for Brochure.dwg REV 10		

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
ALL Dimensions are Nominal

FOR EASY IDENTIFICATION, ALL CELLULAR CORE CONDUIT IS MARKED WITH A BLUE *Powerline*® from spigot to bell