



Southern Pipe	Trade	T Min	OD	E	B	D Min	C	R	L
Part Number	Size	Wall Thickness	Outside Diameter	Bell Entrance ID	Bell Bottom ID	Bell Depth	Chamfer Angle	Reference Mark	Total Length
62820	2"	0.060	2.375	2.387	2.369	2.500	30°	2.500	240
62630	3"	0.061	3.500	3.516	3.492	3.625	30°	3.625	240
62635	3 1/2"	0.072	4.000	4.016	3.992	3.875	30°	3.875	240
62640	4"	0.082	4.500	4.518	4.491	4.125	30°	4.125	240
62650	5"	0.103	5.563	5.583	5.553	4.750	30°	4.750	240
62660	6"	0.125	6.625	6.647	6.614	5.750	30°	5.750	240

 Listed 651
 NEMA TC 6
 Sunlight Resistant
 ASTM F-512
 For Encasment in Concrete

RUS Listed
 NEMA TC 18
 90° C Wire



TC 6 EB-20 Rigid Non-Metallic PVC Utility Duct
 Minimum Modulus of Elasticity 500,000 psi

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES
 All Dimensions are Nominal

	NAME	DATE
DRAWN	K. Mitchell	04/01/13
CHECKED		
ENG APPR		
FILE: TC 6 EB-20.dft		REV 10